



SHENG CHIA

RUBBER INDUSTRY CO., LTD

NO.29-19, HSU, CHOU, KUNG, NAN KUNG TSUN

TA-YUAN, TAOYUAN.TAIWAN.R.O.C.

IMPELLER

IDENTIFICATION GUIDE

URL: <http://www.snchia.com>
 EMAIL : customer@snchia.com
 TEL : (886-3) 3866255
 FAX : (886-3) 3868936

No.	TYPE	CALIBER	OUTSIDE-DIAMETER	HIGHT	INSIDE-DIAMETER	LEAVES QUANTITY	MATERIAL	AXISSHAPE	INESERT MATERIALS	BRONZE LENGTH	KIND OF AXIS	IMPELLER DIMENSIONS
01	500-12C	2 1/2"	127.6	101.6	38	12	CR	C	BR			
02	300-9C	2"	93.1	95.2	25	9	CR	C	BR			
03	280-9C	1 1/2"	93.1	88.6	25	9	CR	C	BR			
04	280-9F2	1 1/2"	93.1	88.6	25	9	CR	F2	BR			
05	220-9C	1 1/2"	93.1	63.5	25	9	CR	C	BR			
06	200-9C	1 1/2"	93.1	63.1	25	9	CR	C	BR			
07	200-9F2	1 1/2"	93.1	63.1	25	9	CR	F2	BR			
08	170-9C	1"	79.5	75.8	20	9	CR	C	BR			
09	100-9C	1"	79.5	54.1	20	9	CR	C	BR			
10	F25-8C	1"	79.5	54.1	20	8	CR	C	BR			
11	F25-8K	1"	79.5	54.1	20	8	CR	K	BR			
12	70-8C	3/4"	65	50.2	15.8	8	CR	C	BR			
13	70-8KN	3/4"	65	50.2	15.8	8	NBR	K	BR			
14	70-10C	3/4"	65	50.2	15.8	10	CR	C	BR			
15	140-9C	1 1/2"	93.1	43.0	20	9	CR	C	BR			



SHENG CHIA

RUBBER INDUSTRY CO., LTD

NO.29-19, HSU, CHOU, KUNG, NAN KUNG TSUN

TA-YUAN, TAOYUAN.TAIWAN.R.O.C.

IMPELLER

IDENTIFICATION GUIDE

URL: <http://www.snchia.com>

EMAIL: customer@snchia.com

TEL: (886-3) 3866255

FAX: (886-3) 3868936

No.	TYPE	CALIBER	OUTSIDE-DIAMETER	HIGHT	INSIDE-DIAMETER	LEAVES QUANTITY	MATERIAL	AXISSHAPE	INESERT MATERIALS	BRONZE LENGTH	KIND OF AXIS	IMPELLER DIMENSIONS
16	150-9C	1 1/2"	93.1	43.0	25	9	CR	C	BR			
17	F20-8C	3/4"	65	36.5	25.3	8	CR	C	BR			
18	NOKY-8KN	1/2"	57	31.7	25.3	8	NBR	K	BR			
19	NOKY-8PN	1/2"	57	31.7	25.3	8	NBR	P	BR			
20	NOKY-12KN	1/2"	57	31.7	25.3	12	NBR	K	BR			
21	NOKY-12CN	1/2"	57	31.7	25.3	12	NBR	C	BR			
22	YS-6PN	1/4"	40.4	19.7	9.52	6	NBR	P	BR			
23	GPS-6PN	3/8	50.7	22.8	12.7	6	NBR	P	BR			
24	GPS-6P	3/8	50.7	22.8	12.7	6	CR	P	SS			
25	114812N	3/8	43	14.4	12.0	6	NBR		NYLON			
26	433915N	3/8	38.6	18.0	11.20	3	NBR		NORYL			
27	110-9C		79.5	63.2	20	9	CR	C	BR			
28	130-10C	T:3.8	65	68	15.8	10	CR	C	BR			
29	70-8CN	T: 5.0	65	50.2	15.8	8	NBR	C	BR			
30	200-10C		95.2	63.5	25	10	CR	C	BR			

